


Standard equipment

- Low-bed Machinery Hauler
- Tag-Along (only)

<p>Width : 78 inches between fenders 102 inches (exterior)</p> <p>Length : 16 or 18 feet (including optional slope)</p> <p>Height : 22 inches</p> <p>Axles : (2) 5200 lb, 6000 lb. or 7000 lb. Torsion Axles</p> <p>Brakes : Electric with Breakaway Kit</p> <p>Coupler : 5-position Adjustable Coupler 2^{5/16}" with security chain and hooks</p>	<p>Jack : 7000 lb. Capacity Topwind</p> <p>Crossmembers : 3" channel crossmembers every 16"</p> <p>Ramps : (2) Hinged loading ramps 16"x 48" with spring assist</p> <p>Floor : Wood Floor 1^{5/8}" thick</p> <p>Finish : Epoxy Primer, Urethane Paint and 2 inch wide reflective tape</p> <p>Colors : Black or Charcoal Grey</p>
---	--



Our wiring system is built for extreme conditions. Standard LED lights



1020, Craig NORTH, Cookshire (Quebec) Canada
 Tel. : 819-875-5326 • 888-875-6326
 Telec. : 819-875-5367
 Email : info@kerrtrailers.com

Available at :

All illustrations and specifications contained in this literature are based on the latest information available at time of publication. Certain equipment shown may be optional. The right is reserved to make changes in materials, equipment, designs, specifications and models.